

BUILT-TO-LAST HYDRAULIC TOOLS FROM RACINE RAILROAD PRODUCTS

Designed specifically for the railroad industry, the Racine Trak-Pak II is a heavy-duty hydraulic power unit that offers 10 GPM flow.

Heavy Duty

The Trak-Pak II is equipped with a 22 HP Honda GX-690 electric start four cycle engine that offers 22% more horse power than other power units on the market. It offers a large 9-gallon hydraulic reservoir and heavy duty oil cooler with thermostatic electric fan to maintain a low hydraulic oil temperature, which will increase tool performance and extend the life of your tools. A heavy gauge steel frame, roll cage and lifting bale are standard for protection of components and easy maneuvering. The large muffler offers excellent sound suppression for a quieter and safer work environment.

Easy Serviceability

The Trak-Pak II comes standard with a combination digital engine hour meter / engine tachometer and hydraulic oil level. Its open design allows easy access to all components including a large hydraulic tank clean out.



Model 910146

Circuit	10 GPM @ 2,000 PSI 38 LPM @ 138 BAR
Length	40 in. / 101.6 cm
Width	24 in. / 60.9 cm
Height	30 in. / 76.2 cm
Weight	380 lb / 172 kg
Engine	Honda GX-690
Fuel Capacity	7 Gallons
Hydraulic Oil Capacity	9 Gallons

Accessories

Wheel Assembly - Bolt on kit that includes flat free type tires, 2 support legs and handle to easily maneuver or transport.

Pressure Gauge Assembly - Kit includes console style 2 ½" gauge, 0-3000 P.S.I., mounting plate and pressure hose to easily read pressure and ensure proper operation

Flow Meter Assembly - Flow Meter Kit: Kit includes 1-15 G.P.M. high pressure flow meter, hoses and couplers to monitor hydraulic flow and ensure the unit is working at peak performance.

Hydraulic Selector Valve Assembly - kit includes manually operated 3-way, 2-position selector valve, mounting plate, two connecting pressure hoses and required quick couplers for work ports.

Directional Control Valve Assembly - kit includes manually operated 4-way, 3-position directional control valve, tandem spool, spring loaded to center position. Also includes mounting plate with hardware, two required connecting pressure hoses and quick couplers for work ports.

12-Volt Solenoid Operated Directional Control Valve Assembly - kit includes DO5 size 4-way, 3-position directional control valve with mounting plate and hardware. Also includes two required connecting pressure hoses, electrical box with connectors, required quick couplers for work ports, A/B handheld pendant on 20-foot cord, fused power supply cable with battery fuse protection.

Visit our web site: www.racinerailroad.com

For a complete list of specifications and machine options available, contact
 Racine Railroad Products, Inc. at: Tel (262) 637-9681 • Fax (262) 637-9069 • email: custserv@racinerailroad.com
 1955 Norwood Court • Mount Pleasant, Wisconsin 53403