SAFETY DATA SHEET

HYDREX ™ XV ALL SEASON



Page: 1 / 10

000003001240

Version 2.4 Revision Date 2020/02/04 Print Date 2020/02/04

SECTION 1. IDENTIFICATION

Product name : HYDREX ™ XV ALL SEASON

Product code : HDXASCBE, HDXASICT, HDXASP5R, HDXASP20,

HDXASIBC, HDXASDRR, HDXASDRM, HDXASDCT,

HDXASC16, HDXAS, HDXASBLK

Manufacturer or supplier's details

Petro-Canada Lubricants Inc. 2310 Lakeshore Road West Mississauga ON L5J 1K2

Canada

Telephone: 1-905-403-6785

Emergency telephone number

Emergency telephone number: CHEMTREC: 1-800-424-9300;

Poison Control Centre: Consult local telephone directory for

emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use : Hydrex XV All Season hydraulic oil is a premium hydraulic oil

designed for year round use in hydraulic systems that are exposed to wide temperature extremes. It is specifically recommended for woodland, mining, construction, public utility and marine operations eliminating the need for seasonal

changeovers.

Prepared by : Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	viscous liquid
Colour	Bright, pale yellow.
Odour	Mild petroleum oil like.

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Potential Health Effects

Primary Routes of Entry : Eye contact

Ingestion Inhalation Skin contact

Aggravated Medical Condi-

on

: None known.



000003001240

Version 2.4 Revision Date 2020/02/04 Print Date 2020/02/04

Other hazards None known.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

No component of this product present at levels greater than or **ACGIH**

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by ACGIH.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	30 - 50
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	30 - 50
2,6-di-tert-butylphenol	128-39-2	0.25 - 1

SECTION 4. FIRST AID MEASURES

Artificial respiration and/or oxygen may be necessary. If inhaled

> Move to fresh air. Seek medical advice.

In case of skin contact In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a physi-

Page: 2 / 10

cian or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms and effects, both acute and First aider needs to protect himself.

delayed

Internet: lubricants.petro-canada.com/sds

TM Owned or used under license.



000003001240

Version 2.4 Revision Date 2020/02/04 Print Date 2020/02/04

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

No information available.

Specific hazards during fire-

fighting

Cool closed containers exposed to fire with water spray.

Hazardous combustion prod: :

ucts

Carbon oxides (CO, CO2), smoke and irritating vapours as

products of incomplete combustion.

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: :

tive equipment and emergency procedures

Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

Environmental precautions : Do not allow uncontrolled discharge of product into the envi-

ronment.

Methods and materials for containment and cleaning up

Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.

Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation.

Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

None known.

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Use only with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Conditions for safe storage : Store in original container.

Internet: lubricants.petro-canada.com/sds

TM Owned or used under license.

Page: 3 / 10



000003001240

Version 2.4 Revision Date 2020/02/04 Print Date 2020/02/04

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct sun-

light.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH

Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-



000003001240

Version 2.4 Revision Date 2020/02/04 Print Date 2020/02/04

essary.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Protective measures : Wash contaminated clothing before re-use.

Hygiene measures : Remove and wash contaminated clothing and gloves, includ-

ing the inside, before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Colour : Bright, pale yellow.

Odour : Mild petroleum oil like.

Odour Threshold : No data available

pH : No data available

Pour point : -48 °C (-54 °F)

Boiling point/boiling range : No data available

Flash point : 227 °C (441 °F)

Method: Cleveland open cup

Fire Point : No data available Evaporation rate : No data available

Auto-ignition temperature : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.8488 kg/l (15 °C / 59 °F)

Solubility(ies)

SAFETY DATA SHEET

HYDREX ™ XV ALL SEASON



000003001240

Version 2.4 Revision Date 2020/02/04 Print Date 2020/02/04

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, kinematic : 47.9 cSt (40 °C / 104 °F)

9.67 cSt (100 °C / 212 °F)

Explosive properties : Do not pressurise, cut, weld, braze, solder, drill, grind or ex-

pose containers to heat or sources of ignition.

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac-

tions

Hazardous polymerisation does not occur.

Stable under normal conditions.

Conditions to avoid : No data available

Incompatible materials : Reactive with oxidising agents and reducing agents.

Hazardous decomposition

products

May release COx, NOx, SOx, POx, H2S, metal oxides, meth-

acrylate monomers, smoke and irritating vapours when heated

to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of:

exposure

Eye contact Ingestion

Inhalation Skin contact

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Components:

lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Internet: lubricants.petro-canada.com/sds

Page: 6 / 10

TM Owned or used under license.



000003001240

Version 2.4 Revision Date 2020/02/04 Print Date 2020/02/04

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

LD50 (Rabbit): > 2,000 mg/kg, Acute dermal toxicity

Skin corrosion/irritation

Product:

Remarks : No data available

Serious eye damage/eye irritation

Product:

No data available Remarks

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

: Remarks: No data available Toxicity to algae

Toxicity to microorganisms : Remarks: No data available

Page: 7 / 10



000003001240

Version 2.4 Revision Date 2020/02/04 Print Date 2020/02/04

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

National Regulations

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

IECSC : On the inventory, or in compliance with the inventory

Page: 8 / 10

SAFETY DATA SHEET

HYDREX ™ XV ALL SEASON



000003001240

Version 2.4 Revision Date 2020/02/04 Print Date 2020/02/04

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

For Copy of SDS : Internet: lubricants.petro-canada.com/sds

Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-

4518

Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-

800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax:

1-800-201-6285

For Product Safety Information: 1 905-491-0565



Page: 10 / 10

000003001240

Version 2.4 Revision Date 2020/02/04 Print Date 2020/02/04

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2020/02/04

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN